

CLAIMS:

1. A collimating device for controlling a radiation field of an X-ray radiated from an X-ray radiator, the device comprising:

5 a first plurality of collimating leaves;
a second plurality of collimating leaves opposing the first plurality of collimating leaves;

a beam generator configured to generate a beam which emanates between the first and second plurality
10 of collimating leaves;

a detector configured to detect the beam;

a memory configured to store position information of each leaf of the first and second plurality of collimating leaves when said each leaf is determined
15 to intersect the beam based on the detection; and

a controller configured to position said each leaf based on the position information to control the radiation field.

20 2. The device according to claim 1, further comprising:

a reflector configured to reflect the beam generated by the beam generator so that the reflected beam emanates between the first and second plurality
25 of collimating leaves.

3. The device according to claim 1, further comprising:

a reflector configured to reflect the beam emanated between the first and second plurality of collimating leaves so that the reflected beam is detected by the detector.

4. The device according to claim 1, wherein the memory stores the position information when the detector detects a predetermined percentage of the beam.

5. The device according to claim 1, further comprising:

a compensation unit configured to compensate the position information, wherein the controller positions said each leaf based on the compensated position information.

6. The device according to claim 5, wherein the compensation unit compensates the position information in accordance with an incident angle of the beam between the first and second plurality of collimating leaves.

7. The device according to claim 5, wherein

the memory is further configured to store the compensated position information.

8. The device according to claim 1, further comprising:

a second memory configured to store compensation distance information for compensating the position information, wherein the compensation distance information is based on a distance caused by a gear engagement in a gear rotation when said each leaf is driven by a gear.

9. The device according to claim 8, wherein the second memory stores first distance information and second distance information as the compensation distance information;

the first distance information is used when said each leaf is driven to move by a first predetermined distance in a first direction; and

the second distance information is used when said each leaf is driven to move by a second predetermined distance in a second direction.

10. A collimating device for controlling a radiation field of an X-ray radiated from an X-ray radiator, the device comprising:

a first plurality of collimating leaves;

a second plurality of collimating leaves opposing
the first plurality of collimating leaves;

a beam generator configured to generate at least
5 first and second beams, wherein the first beam intersects
the first plurality of collimating leaves and the second
beam intersects the second plurality of collimating
leaves;

a detector configured to detect the first and
10 second beams;

a memory configured to store first position
information of each leaf of said first plurality of
collimating leaves when each leaf of said first plurality
of collimating leaves is determined to intersect the
15 first beam based on the detection;

said memory further configured to store second
position information of each leaf of said second
plurality of collimating leaves when each leaf of said
second plurality of collimating leaves is determined
20 to intersect the second beam based on the detection;
and

a controller configured to position said each leaf
of said first plurality of collimating leaves based on
the first position information and the each leaf of said
25 second plurality of collimating leaves based on the
second position information so as to control the

radiation field.

11. The device according to claim 10, wherein
the beam generator generates a third beam which
5 emanates between the first and second plurality of
collimating leaves and intersects an axis of the X-ray;
the detector is further configured to detect the
third beam;

the memory is further configured to store third
10 position information of each leaf of the first and second
plurality of collimating leaves when said each leaf is
determined to intersect the third beam based on the
detection; and

the controller is configured to position said each
15 leaf based on the third position information in addition
to the first and second position information.

12. The device according to claim 10, wherein
the beam generator generates third and fourth
20 beams which emanate between the first plurality of
collimating leaves and the second plurality of
collimating leaves, the third beam intersecting the
first plurality of collimating leaves and the fourth
beam intersecting the second plurality of collimating
25 leaves;

the detector is further configured to detect the

third and fourth beams;

the memory is further configured to store the first position information when said each leaf of the first plurality of collimating leaves is positioned furthest
5 from the second plurality of collimating leaves and determined to intersect the first beam with one side far from the second plurality of collimating leaves based on the detection;

said memory further configured to store the second
10 position information when said each leaf of the second plurality of collimating leaves is positioned furthest from the first plurality of collimating leaves and determined to intersect the second beam with one side furthest from the first plurality of collimating leaves
15 based on the detection;

said memory further configured to store third position information when said each leaf of said first plurality of collimating leaves is positioned closest to the second plurality of collimating leaves and
20 determined to intersect the third beam with another side closest to the second plurality of collimating leaves based on the detection;

said memory further configured to store fourth position information when said each leaf of said second
25 plurality of collimating leaves is positioned closest to the first plurality of collimating leaves and

determined to intersect the fourth beam with another side closest to the first collimating leaves based on the detection; and

the controller is configured to position said
5 each leaf of said first plurality of collimating leaves based on the first and third position information and the said each leaf of said second plurality of collimating leaves based on the second and fourth position information.

10

13. The device according to claim 10, wherein
the beam generator generates a first group of beams including the first beam and a second group of beams including the second beam as the plurality of beams,
15 the first group of beams intersecting the first plurality of collimating leaves and the second group of beams intersecting the second plurality of collimating leaves;

the detector is further configured to detect the
20 first and second groups of beams;

the memory configured to store first information of positions of each leaf of said first plurality of collimating leaves where said each leaf of said first plurality of collimating leaves is determined to
25 intersect the first group of beams with one side close to the second plurality of collimating leaves based on

the detection;

said memory further configured to store second information of positions of each leaf of said second plurality of collimating leaves where said each leaf
5 of said second plurality of collimating leaves is determined to intersect the second group of beams with one side close to the first plurality of collimating leaves based on the detection; and

a controller configured to position said each leaf
10 of said first plurality of collimating leaves based on the first information and said each leaf of said second plurality of collimating leaves based on the second information.

15 14. A radiotherapy apparatus for radiating an X-ray and concentrating the X-ray towards a predetermined part of an object, the apparatus comprising:

an X-ray radiator configured to radiate the X-ray;
20 and

a collimator configured to control a radiation field of the X-ray radiated by the X-ray radiator, including:

a first plurality of collimating leaves;
25 a second plurality of collimating leaves opposing the first plurality of collimating leaves;

a beam generator configured to generate a beam which emanates between the first and second plurality of collimating leaves;

a detector configured to detect the beam;

5 a memory configured to store position information of each leaf of the first and second plurality of collimating leaves when said each leaf is determined to intersect the beam based on the detection; and

a controller configured to position said each leaf
10 based on the position information.

15. The apparatus according to claim 14, further comprising:

a display configured to display information of the
15 collimator.

16. The apparatus according to claim 14, wherein the beam generator is rendered operative when said apparatus is powered.

20

17. The apparatus according to claim 14, wherein the beam generator is rendered operative at predetermined intervals.

25

18. The apparatus according to claim 14, further comprising an input unit configured to input an

instruction, wherein the beam generator is rendered operative in response to the instruction.

19. A method of positioning collimating leaves
5 for use in a collimator which controls a radiation field of an X-ray radiated from an X-ray radiator, wherein the collimating leaves include a first and second plurality of collimating leaves, said plurality of second collimating leaves opposing the first plurality of collimating leaves, the method comprising:

generating a beam which emanates between the first and second plurality of collimating leaves;

detecting the beam;

15 storing position information of each leaf of the first and second plurality of collimating leaves when said each leaf is determined to intersect the beam based on the detection; and

positioning said each leaf based on the position information to control the radiation field.

20

20. A method of positioning collimating leaves for use in a collimator which controls a radiation field of an X-ray radiated from an X-ray radiator, wherein the collimating leaves include a first and second
25 plurality of collimating leaves, the plurality of second collimating leaves opposing the first plurality of

collimating leaves, the method comprising:

generating at least first and second beams,
wherein the first beam intersects the first plurality
of collimating leaves and the second beam intersects
5 the second plurality of collimating leaves;

detecting the first and second beams;

storing first position information of each leaf
of said first plurality of collimating leaves when said
each leaf of said first plurality of collimating leaves
10 is determined to intersect the first beam based on the
detection and storing second position information when
each leaf of said second plurality of collimating leaves
is determined to intersect the second beam based on the
detection; and

15 positioning said each leaf of said first plurality
of collimating leaves based on the first position
information and said each leaf of said second plurality
of collimating leaves based on the second position
information to control the radiation field.

20

21. The device according to claim 1, wherein the
beam intersects an axis of the X-ray.